

Seznam žádostí o autonomní celní suspenze a kvóty - období platnosti od července 2023

1. kvóty

KN	TARIC	Číslo žádosti	Popis	Objem kvóty	Nová žádost/žádost o změnu	Pozn.
1518 00 95		6490824/2022	Used Cooking Oil made of: - Fatty acid triglyceride (CAS RN 92128-39-7), and - Fatty acids, vegetable oil (CAS RN 61788-66-7)	Q/1000000tonnes, 01.07-31.12	Nová žádost	component biodiesel
2710 12 21		6485651/2022	Alkenes, C10-14-branched and linear, C12-rich (CAS RN 93821-12-6)	Q/1500tonnes, 01.07-31.12	Nová žádost	Component for polymers production
2815 12 00		6756412/2022	Sodium hydroxide [membrane class] (CAS RN 1310-73-2) in form of an aqueous solution with a content of sodium hydroxide by weight of 48 % or more but not more than 51 %	Q/350000tonnes, 01.07-31.12	Nová žádost	For use in textile industry
2840 20 90		6836516/2022	Barium diboron tetraoxide (CAS RN 13701-59-2)	Q/130tonnes, 01.07-31.12	Nová žádost	Round 2023-07: used in coatings as corrosion inhibitor etc.
2905 39 95		6790870/2022 6791056/2022	Propane-1,3-diol (CAS RN 504-63-2) of a purity of 99 % or more	Q/1550tonnes, 01.07-31.12	Nová žádost	Round 2023-07: Used in cosmetic industry, including hair care, skin care, body cleansing, makeup, deodorants, baby care, sunscreen, pharmaceutical products.
3824 99 92		6836269/2022	Amides, tall-oil fatty, N,N-di-Me (CAS RN 68308-74-7)	Q/180tonnes, 01.07-31.12	Nová žádost	Round 2023-07 used as a non-biocidal component in biocidal products applied in the pulp and paper industry and in leather treatment

3912 39 85		6759171/2022	Hypromellose (INN) (CAS RN 9004-65-3), for use in the manufacturing of food, food supplements, beverages or pharmaceuticals (1)	Q/2350tonnes, 01.07-31.12	Nová žádost	Round 2023-07: for use in the manufacturing of food, food supplements, beverages or pharmaceuticals
2903 21 00		2258441/2022	NL + FR 10.5.22 Chloroethylene (CAS RN 75-01-4) with a purity by weight of 99 % or more --- Vinyl Chloride, Chloroethylene (Vinyl Chloride Monomer, VCM) (CAS RN 75-01-4)	Q/37500000kilograms, 01.01-31.12	Žádost o změnu	Round 2023-07 - roll over request./ Round 2023-01 - Request for TR national quota - Rejected. Used in various applications such as blow molding of bottles and containers, in the production of pipes etc.
8414 30 81		1097/2007 TR	Rotary type compressor, consisting of a single phase or three phase motor with a cooling capacity range between 2Kw to 8Kw, using a refrigerant fluid of type R32 or R410, for use in the manufacture of air conditioning machines (1)	Q/2000000pieces, 01.01-31.12	Žádost o změnu	Round 2023-07 - Roll-over request for increase.// Round 2023-01 - Request for increase (TR national quota)/ REJECTED Round 2020-07 - Request for increase (TR national quota)/ Round 2019-07 - Request for amendment (TR national quota)
ex 8482 99 00	30	1518429/2018	Brass cages with the following characteristics: - continuously or centrifugally cast, - turned, - containing by weight 35 % or more, but not more than 38 % of zinc, - containing by weight 0,75 % or more, but not more than 1,25 % of lead, - containing by weight 1,0 % or more, but not more than 1,4 % of aluminium, and - with a tensile strength of 415 Pa or more, of a kind used for the manufacture of ball bearings	Q/100000pieces, 01.01-31.12	Žádost o změnu	Round 2023-07- request for increase from 50 000 to 100 000 p/st per year. Round 2020-07 - Accepted without any changes. Opened for internal technical reason. Round 2020-01 request for amendment Round 2019-01 accepted during 2nd ETQG meeting the cages are used for the production of ball bearings
ex 8482 99 00	50	4921841/2020	DE(15.09.2023) request for amendment:	Q/12000000kilograms, 01.07-31.12	Žádost o změnu	Round 2023-07 - request for amendment.

			<p>Inner and/or outer rings made of steel, not hardened, outer ring with internal raceway(s), inner ring with external raceway(s), with external diameters of:</p> <ul style="list-style-type: none"> - 14 mm or more but not more than 77 mm for the inner ring, - 26 mm or more but not more than 101 mm for the outer ring <p>---</p> <p>Current text: Inner and outer rings made of steel, not grinded, outer ring with internal raceway(s), inner ring with an external raceway(s), with external diameters of:</p> <ul style="list-style-type: none"> - 14 mm or more but not more than 77 mm for the inner ring, and - 26 mm or more but not more than 101 mm for the outer ring <p>for use in the manufacture of bearings (1)</p>			<p>Round 2023-01 - Roll over request. Quota set to 12 mil kg for 6 months). Round 2022-07 - The suspension with serial number 0.8088 will be set to deleted. A quota will open for the period 01.07-31.12.2022, with quota volume - 10 million kg. Round 2021-07 of a kind used for the production of one raceway ball bearing</p>
--	--	--	--	--	--	---

2. Celní suspenze

KN	TARIC	Číslo žádosti	Popis	Nová žádost/žádost o změnu	Pozn.
1511 90 91		6490591/2022	Refined bleached deodorized palm oil (CAS RN 8002-75-3)	Nová žádost	Component for biodiesel production
1518 00 99		2241226/2022	Mix of: - oil from palm mill effluents: Crude Oil from Palm Oil Mill Effluent; and - oil from the pressing of empty palm fruit bunches: Crude Oil from Empty Fruit Bunch Pressing Process – EFB.	Nová žádost	Round 2023-07: roll-over request. Classification issue./ Round 2023-01 used as raw material for the manufacture of biofuels
2835 10 00		6146075/2022	Calcium Hypophosphite (CAS RN 7789-79-9) with a purity by weight of 98 % or more	Nová žádost	Round 2023/7 product is incorporated as an additive
2903 99 80		6790600/2022	1-fluoronaphthalene (CAS RN 321-38-0) with a purity by weight of 99,5 % or more	Nová žádost	For use in pharmaceutical industry
2907 29 00		6707958/2022	Tetramethyl bisphenol F (CAS 5384-21-4) of a purity by weight of 98,5 % or more	Nová žádost	Component for packaging industry
2811 22 00		7079710/2022	Mercaptoalkyl 4 silica (CAS RN N/A) with a purity by weight of 98 % or more	Nová žádost	Round 2023-07: Works as a metal scavenger
2914 79 00		6489056/2022	(S)-2-amino-2-(3-fluoro-5-methoxyphenyl)ethanol hydrochloride (CAS RN 2095692-22-9) with a purity by weight of 98 % or more	Nová žádost	Component for pharmaceutical industry
2915 90 30		6574944/2022	Dodecanoic acid chloromethyl ester (CAS No 61413-67-0) with a purity by weight of 97 % or more	Nová žádost	Component for pharmaceutical industry
2915 90 70		6396465/2022	3-chloro-2,2-dimethylpropanoyl chloride (CAS RN 4300-97-4) with a purity by weight of 98,5 % or more	Nová žádost	Substance for plant protection industry

2916 39 90		6754449/2022	Ethyl 4-bromo-3-(bromomethyl)benzoate (CAS RN 347852-72-6) with a purity by weight of 97 % or more	Nová žádost	Used for pharmaceutical production
2918 19 98		6642626/2022	(S)-2-hydroxy-2-phenylacetic acid (CAS RN 17199-29-0) with a purity by weight of 99 % or more	Nová žádost	Component for pharmaceutical industry
2920 90 10		6705077/2022	Diethyl carbonate (CAS RN 105-58-8) with a purity by weight of 99.9 % or more	Nová žádost	Component for battery industry
2921 19 99		6492822/2022	N-Ethyl-N-isopropylpropan-2-amine 2-(difluoromethoxy)acetate with a purity by weight of 98 % or more.	Nová žádost	
2926 90 70		6480148/2022	Reaction product comprising equal quantities of - a-cyano-3-phenoxybenzyl (Z)-(1R,3R)-3-(2-chloro-3,3,3-trifluoroprop-1-enyl)-2,2-dimethylcyclopropanecarboxylate and - a-cyano-3-phenoxybenzyl (Z)-(1S,3S)-3-(2-chloro-3,3,3-trifluoroprop-1-enyl)-2,2-dimethylcyclopropanecarboxylate, (CAS RN 91465-08-6) with a purity by weight of 97 % or more	Nová žádost	Component for plant protection industry
2928 00 90		6489127/2022	Ethyl chloro[(4-methoxyphenyl)hydrazono]acetate (CAS RN 27143-07-3) with a purity by weight of 98 % or more	Nová žádost	Component for pharmaceutical industry
2929 10 00		6159652/2022	Ethyl Isocyanate (CAS RN 109-90-0) with a purity by weight of 98 % or more	Nová žádost	Round 2023/07 used for pharmaceutical production
2930 90 98		6146033/2022	Thiodiacetic acid (CAS RN 123-93-3) with a purity by weight of 98 % or more	Nová žádost	Round 2023/7 The intermediate is used as a raw material in the chemical synthesis of an active ingredient
2930 90 98		6642658/2022	Potassium salt of O-isopentyl-dithiocarbonate with a purity by weight of 90 % or more, dry, in pellets.	Nová žádost	Product for mining industry
2930 90 98		6541059/2022	2,2'-Diallyl-4,4'-sulphonyldiphenol (CAS RN 41481-66-7), with a purity by weight of 96 % or more	Nová žádost	Component for paper industry
2931 20 00		6606957/2022	Tributyltin chloride (CAS RN 1461-22-9) of a purity by weight of 80 % or more	Nová žádost	Component for pharmaceutical industry

2932 20 90		6540912/2022	(R)-3-(3,4-difluoro-2-methoxyphenyl)-4,5-dimethyl-5-(trifluoromethyl)furan-2(5H)-one with a purity by weight of 98 % or more	Nová žádost	Component for pharmaceutical industry
2933 29 90		6159573/2022	4-chloro-2-cyano-N,N-dimethyl-5-p-tolylimidazole-1-sulfonamide (CAS RN 120116-88-3) with a purity by weight of 94 % or more	Nová žádost	Round 2023/07 used for pesticides products
2933 39 99		6720201/2022	Fluazinam technical (CAS RN 79622-59-6) with a purity by weight of 97 % or more	Nová žádost	Used for production of fungicides
2933 59 95		6708187/2022	1,4,5,6-tetrahydro-1,2-dimethylpyrimidine (CAS RN 4271-96-9) with a purity by weight of 98 % or more	Nová žádost	Used for human pharmaceutical industry
2933 59 95		6393588/2022	5-Chloro-3-nitropyrzolo[1,5-a]pyrimidine (CAS RN 1363380-51-1) with a purity by weight of 98 % or more	Nová žádost	Substance for pharmaceutical industry
2933 59 95		6753587/2022	Active Pharmaceutical Ingredient: Trilaciclib (INN) (CAS RN 1374743-00-6) with a purity by weight of 99,8 % or more	Nová žádost	Used for pharmaceutical production
2933 79 00		6488997/2022	R)-tert-butyl 2-(6-(5-chloro-2-((tetrahydro-2H-pyran-4-yl)amino)pyrimidin-4-yl)-1-oxoisindolin-2-yl)propanoate (CAS RN 2095665-45-3) with a purity by weight of 98 % or more	Nová žádost	Product for pharmaceutical industry
2933 99 20		6393527	4-([1,2,4]triazolo[1,5-a]pyrid-7-yloxy)-3-methylaniline (CAS RN 937263-71-3) with a purity by weight of 98 % or more	Nová žádost	Componant for pharmaceutical industry
2934 99 90		6159360/2022	3-[2-((2R,3S)-3-[(1R)-1-[[tert-butyl(dimethyl)silyl]oxy]ethyl]-4-oxoazetid-2-yl)propanoyl]-4,4-dimethyl-1,3-oxazolidin-2-one (CAS RN 114341-89-8) with a purity by weight of 79 % or more	Nová žádost	Round 2023/7 Use and type of product into which it is to be incorporated: Antibiotic production through chemical synthesis
2934 99 90		6746463/2022	Cedazuridine (INN) (CAS RN 1141397-80-9) with a purity by weight of 99,0 % or more	Nová žádost	Used for pharmaceutical production
2935 90 90		6899888/2022	5-(2-fluorophenyl)-1-(pyridin-3-ylsulfonyl)-1H-pyrrole-3-carbaldehyde (CAS RN 881677-11-8)	Nová žádost	Round 2023-07: for the manufactured of pharmaceutical.

2935 90 90		6540956/2022	2-Bromo-N-(4,5-dimethyl-1,2-oxazol-3-yl)-N-(methoxymethyl) benzene-1-sulfonamide (CAS RN 415697-57-3) with a purity by weight of 97 % or more	Nová žádost	Component for pharmaceutical industry
2935 90 90		6899888/2022	Sulfonamid; 5-(2-Fluorophenyl)-1-(pyridin-3-ylsulfonyl)-1H-pyrrol-3-carbaldehyd, commonly known as PSPA or 5-(2-Fluorophenyl)-1-(3-pyridylsulfonyl)pyrrole-3-carbaldehyde (Synonym)	Nová žádost	For use in pharmaceutical industry
2942 00 00		6754544/2022	4,4,5,5-Tetramethyl-1,3,2-dioxaborolane (CAS RN 25015-63-8) with a purity by weight of 97,5 % or more, with not more than 1 % of the stabiliser triethylamine (CAS RN 121-44-8)	Nová žádost	Used for pharmaceutical production
3824 99 92		6480217/2022	Reaction mass of 3-methylphenyl diphenyl phosphate (CAS RN 69500-28-3), 4-methylphenyl diphenyl phosphate (CAS RN 78-31-9), bis(3-methylphenyl) phenyl phosphate (CAS RN 34909-68-7), 3-methylphenyl 4-methylphenyl phenyl phosphate (CAS RN 222165-66-4) and triphenyl phosphate (CAS RN 115-86-6)	Nová žádost	Component flame retardant
3824 99 92		6745332/2022	Mixture of tetrabutyltin (CAS RN 1461-25-2), with a content of not more than 75 %, and tributyltin chloride (CAS RN 1461-22-9) of not more than 20 % by weight and dibutyltin dichloride (CAS RN 683-18-1) of not more than 4 % by weight	Nová žádost	For use in glass production / used as a catalyst in the pharmaceutical industry
3824 99 92		6486110/2022	Amines, tri-C8-10-alkyl (CAS RN 68814-95-9)	Nová žádost	
3824 99 96		6606836/2022	Preparation containing by weight 60 % or more but not more than 70 % of 1,2-Cyclohexanedicarboxylic acid, calcium salt (1:1), (1R, 2S)-rel- (CAS 491589-22-1) and 30 % or more but not more than 40 % of Zinc Stearate (CAS 557-05-1)	Nová žádost	Substance for polymer production
3824 99 96		6606893/2022	Preparation containing by weight 60 % or more but not more than 70 % of 1,2-Cyclohexanedicarboxylic acid, calcium salt (1:1), (1R, 2S)-rel- (CAS 491589-22-1), 30 % or more but not more than 40 % of Zinc Stearate (CAS 557-05-1), 1 % or more but not more than 5 % CI Pigment Blue 29 (CAS	Nová žádost	Component for polymer industry

			57455-37-5) and 1 % or more but not more than 5 % CI Pigment Violet 15 (CAS 12769-96-9).		
3907 29 99		6789897/2022	Poly(oxy-1,4-phenyleneoxy-1,4-phenylenecarbonyl-1,4-phenylene) (CAS RN 29658-26-2) containing by weight not more than 35 % of additives	Nová žádost	Round 2023-07 :Used in production of Aircraft Applications; Automotive Applications; Dental Applications; Electrical/Electronic Applications; Film; Gears; Hospital Goods; Housings; Industrial Applications; Medical/Healthcare Applications; Oil/Gas Applications; Profiles; Rods; Sheet; Semiconductor Applications
3920 62 19		6707528/2022	Non-transparent poly (ethylene terephthalate) film <ul style="list-style-type: none"> - Coated on both sides with polyvinylidene difluoride / Polyvinyl fluoride based on fluorinated polymer composites 25 µm thick but not more than 27.5 µm and inner (core) PET 250 µm thick but not more than 275 µm - With peel strength equal to or greater than 60N/1.5 cm (as determined by ASTM D-903) - With a tensile strength equal to or greater than 10000 N/cm² (100MPa) (as determined by the ASTM D-882method) - With a total thickness of 300 µm or more but not more than 320 µm, - With 1036 mm or more but not more than 1040 mm 	Nová žádost	Product for renewable energy industry
4009 12 00		6707696/2022	Multilayer rubber and aramid inner layer connection elements, whether or not having polyamide connection elements and steel clamp, used in automotive heat exchangers and/or condenser in automotive air conditioning systems (1)	Nová žádost	Used in automotive industry
7326 90 98		6707449/2022	Disc of a kind used in turbochargers for ensuring the gas flow channel width: <ul style="list-style-type: none"> - of iron or steel alloy, - with a heat resistance of 830 °C or more but not more than 1050 °C, - with an external diameter of not more than 92.5 mm, - with an internal diameter of not more than 62 mm 	Nová žádost	Parts for automotive industry

7326 90 98		6540980/2022	<p>Vane ring of a kind used in turbochargers for fastening gas flow control blades: of iron or steel alloy,</p> <ul style="list-style-type: none"> - with a heat resistance of 830 °C or more but not more than 1050 °C, - with an external diameter of not more than 92 mm, - with holes for holding the gas flow control blades 	Nová žádost	Parts for automotive industry
7608 20 89		6707627/2022	<p>Bent connection tubes used in turbocharged air cooling systems:</p> <ul style="list-style-type: none"> - with integrated aluminium quick coupler, - with oval bent connection side - made of aluminum alloy 3103 and/or 6060 <p>(1)</p>	Nová žádost	Used in automotive industry
7609 00 00 8708 91 99		6480273/2022	<p>Flame brazed aluminium block for connecting tubes in automotive heat exchangers and/or turbocharged air coolers and/or automatic transmission coolers:</p> <ul style="list-style-type: none"> - with extruded, bent connection tubes with an outer diameter of 5 mm or more, but not more than 25 mm, - with a mass of 0,02 kg or more, but not more than 0,25 kg, <p>for use in the manufacture cooling system in vehicles of chapter 87</p> <p>(1)</p>	Nová žádost	Parts for automotive industry
7609 00 00 8415 90 00		6800405/2022	<p>Aluminium connection block for the manufacture of automotive cooling and air conditioning systems:</p> <ul style="list-style-type: none"> - weighing of 3 g or more, but not more than 400 g, - manufactured from 6061-t6 or 6060-t6 or 6082-t6 aluminium grade, - being an integral part of an air conditioning hose assembly or oil cooling line hose assembly or air brake line hose assembly or water cooling line hose assembly, - having holes (sockets) or splines (pilots) or threads that allow installation in an automotive or other air conditioning system (also understood as installation in the line), - with sockets designed for brazing or fastening, - with at least 1 through-hole with a diameter of 3 mm or more, but not more than 25 mm 	Nová žádost	For use in the automotive industry
7609 00 00		6707825/2022	Machined aluminium components:	Nová žádost	For use in automotive industry

			<ul style="list-style-type: none"> - with an amount of magnesium of 0,55 %, or more but not more than 0,61 % - with an amount of silicon of 0,55 %, or more but not more than 0,61 % - with a hardening state of T5 or T6 - with a mass of 0,05 kg or more, but not more than 0,2 kg <p>used in CO2 cooling systems in motor vehicles (1)</p>		
8105 90 00		6459858/2022	<p>Strip-shape ductile cobalt, with a:</p> <ul style="list-style-type: none"> - width of 10,1 mm or more, but not more 10,3 mm, - thickness of 0,23 mm or more, but not more than 0,27 mm, and - length of 300 m or more, but not more 2 560 m 	Nová žádost	Component for metallurgical industry
8409 91 00		6483017/2022	<p>Camshaft carrier for a spark-ignition piston internal combustion engine, made of ADC12 aluminium alloy, with:</p> <ul style="list-style-type: none"> - weight of 4,0 kg or more but not more than 5,5 kg, - wall thickness of 2,0 mm or more but not more than 6,0 mm, <p>for use in the manufacture of motor vehicle engines (1)</p>	Nová žádost	Parts for the automotive industry
8409 91 00		6484103/2022	<p>Crankcase for 4-cylinder spark-ignition piston internal combustion engine, made of ADC12 aluminium alloy, for use in the manufacture of motor vehicle engines (2) (1)</p>	Nová žádost	Parts for automotive industry
8414 90 00		6830561/2022	<p>Scroll type compressor housing of an aluminium alloy of a kind used in turbochargers with:</p> <ul style="list-style-type: none"> - a heat resistance of 200 °C or more but not more than 250 °C, - a surface suitable for mounting an actuator 	Nová žádost	For use in automotive industry
8414 90 00		6708104/2022	<p>Fan assy made of aluminium and magnesium alloy:</p> <ul style="list-style-type: none"> - with an outer diameter 54 mm or more but not more than 130 mm, - with a height of 8 mm or more but not more than 30 mm, - two discs connected by blades of involute shape, - with or without dowel, and - with or without washer 	Nová žádost	Parts for motor manufacture

8415 90 00		6480335/2022	<p>Electrically welded manifolds for the condenser in automotive air conditioning systems:</p> <ul style="list-style-type: none"> - consisting of a tube produced by stamping an aluminium strip and joining by electric arc welding, - containing internal baffles responsible for the proper flow of coolant, - with a length of 190 mm or more, but not more than 460 mm, - with a diameter of 9 mm or more, but not more than 42 mm, - with a weight of 0,01 kg or more, but not more than 0,45 kg, - whether or not having aluminium connection blocks <p>for use in the manufacture of air conditioning systems in vehicles of chapter 87 (1)</p>	Nová žádost	
8501 32 00		7080081/2022	<p>FUEL CELL MODULE. The module has a PEM fuel cell with a DC/DC converter with an output between 60/80 kW in a voltage range of 400 to 750 V It also contains an air compressor, a water pump, and a hydrogen pump. Hydrogen tank and high voltage battery are not included. 850132 Of an output exceeding 750 W but not exceeding 75 kW Electric motors and generators (excluding generating sets) - Toyota fuel cell module is a DC Generator, exceeding 750 W, but not exceeding 75kW, not Aircraft</p>	Nová žádost	Round 2023-07: battery related product
8501 33 00		7079843/2022	<p>FUEL CELL MODULE The module has a PEM fuel cell with a DC/DC converter with an output between 60/80 kW in a voltage range of 400 to 750 V It also contains an air compressor, a water pump, and a hydrogen pump. Hydrogen tank and high voltage battery are not included. 850133 Of an output exceeding 75 kW but not exceeding 375 kW Electric motors and generators (excluding generating sets) - Toyota fuel cell module is a DC Generator, exceeding 75 kW, not exceeding 375 kW Not Aircraft, not drive motor for motor vehicle, not AC or DC motor</p>	Nová žádost	Round 2023-07: battery related
8501 53 50		6404155/2022	<p>Asynchronous traction motor, with:</p> <ul style="list-style-type: none"> - a continuous power of 140 kW or more but not more than 180 kW, - a liquid cooled system, - a total length of 580 mm or more but not more than 730 mm, - a total width of 550 mm or more but not more than 670 mm, - a total height of 510 mm or more but not more than 630 mm, - weighing of not more than 390 kg, 	Nová žádost	parts for automotive industry

			- 2 mounting points		
8505 11 00		6620328/2022	Two magnets in a rectangular steel holder with an outer casing of rubber with outer dimensions: <ul style="list-style-type: none"> - a length of 200 mm or more but not more than 205 mm - a width of 58 mm or more but not more than 62 mm - a height of 25 or more but not more than 30 with a stud mounted in the middle	Nová žádost	Parts for renewable energy sector
8512 30 90		6374014/2022	Device for simulating engine sound at reduced speed of a hybrid or electric vehicle: <ul style="list-style-type: none"> - containing at least printed circuit board and loudspeaker, - in a plastic housing with a holder, for use in the manufacture of goods of Chapter 87 (1)	Nová žádost	Parts for cars
8512 90 90		6374151/2022	Ultrasonic parking sensor, with voltage of 9 VDC or more, but not more than 16 VDC (direct current voltage), with ability to detect by the ultrasonic method the presence of an object behind and in front of the vehicle, consisting at least of: <ul style="list-style-type: none"> - a transmitter, - a receiver, - a control unit, - a connector, for use in the manufacture of goods of Chapter 87 (1)	Nová žádost	Parts for automotive industry
8537 10 91		6460984/2022	Electronic suspension control unit with: <ul style="list-style-type: none"> - printed circuit board in plastic housing, - LIN and CAN buses, - memories, - signal processor, - an operating voltage of 9 VDC or more, but not more than 16 VDC (direct current voltage), - at least one connector, - whether or not with metal mounting bracket, for use in the manufacture of goods of Chapter 87 (1)	Nová žádost	Parts for automotive industry

8708 50 20		6461042/2022	Propeller shaft for torque transmission from the gearbox to the rear axle, consisting of: <ul style="list-style-type: none"> - two cardan rods, - central universal joint, - central bearing with suspension in a plastic cover, - universal joints on both ends of the shaft - slip, tube and end yokes, - of a length of 1,4 m or more but not more than 2,4 m for use in the production of goods of Chapter 87 (1)	Nová žádost	Parts for automotive industry
8714 99 90		6607668/2022	Rear air shock absorber for use in the manufacture of bicycles, including electrical bicycles, under CN codes 87120030 and 87116010 (1)	Nová žádost	Parts for bike production

ex 2914 29 00 3824 99 92	80	4503840/2017	1-(Cedr-8-en-9-yl)ethanone (CAS RN 32388-55-9)	Žádost o změnu	Round 2023-07: Request for amendment.// Round 2023-01 - prolongation + amendment// Round 2018-07 -For the production of fragrances
ex 2915 90 70	38	6013563/2021	Pelargonic acid (CAS RN 112-05-0) with a purity by weight of 95 % or more	Žádost o změnu	Round 2023-07 - Objection.// Round 2022/07 Pelargonic acid (n-nonanoic acid) for the production of OXLUBE L9-TMP, end-use as raw material, including for the manufacture of lubricants
ex 2934 99 90 ex 3204 20 00	76 10	821/06 PROLONG 2022	2,5-Thiophenediylbis(5-tert-butyl-1,3-benzoxazole) (CAS RN 7128-64-5)	Žádost o změnu	Round 2023-07 - request for single classification under 32042000. Prolongation Exercise 2022-01-01 Prolongation Exercise 2017-01-01 trade name : Optiblanc PL
ex 3601 00 00	20	164630/2010	PL(12.09.2022):request for amendment	Žádost o změnu	Round 2023-07: request for amendment.

		PROLONG 2022	<p>Pyrotechnical mixture in cylindrical shape or granulate form, composed of strontium nitrate or copper nitrate or basic copper nitrate in a matrix of nitroguanidine or guanidine nitrate, also containing a binder and additives, used as a component of airbag inflators</p> <p>---</p> <p>Current text: Pyrotechnical mixture in cylindrical shape or granulate form, composed of strontium nitrate or copper nitrate in a matrix of nitroguanidine or guanidine nitrate, also containing a binder and additives, used as a component of airbag inflators (1)</p>		The material is used to manufacture gas generators for automobiles. The gas generators are used for Airbags
ex 3903 90 90	86	1201/2008 PROLONG 2019	<p>NL(13.09.2022) request for amendment: Mixture containing by weight:</p> <ul style="list-style-type: none"> - 45 % or more but not more than 65 % of polymers of styrene, - 30 % or more but not more than 45 % of poly(phenylene ether), - not more than 11 % of additives <p>---</p> <p>Current text: Mixture containing by weight:</p> <ul style="list-style-type: none"> - 45 % or more but not more than 65 % of polymers of styrene - 35 % or more but not more than 45 % of poly(phenylene ether) - not more than 10 % of other additives <p>and with one or more of the following special colour effects:</p> <ul style="list-style-type: none"> - metallic or pearlescent with a visual angular metamerism caused by at least 0,3 % flake-based pigment - fluorescent, as characterized by emitting light during absorption of ultraviolet radiation - bright white, as characterized by L* not less than 92 and b* not more than 2 and a* between -5 and 7 on the CIELab colour scale 	Žádost o změnu	Round 2023-07: request for amendment./ Prolongation Exercise 2019-01-01 Prolongation Exercise 1/1/2014
ex 3907 29 20	50	824715/2014 PROLONG 2020	<p>NL(13.09.2022) request for amendment: Poly(p-phenylene oxide) in the form of powder</p> <ul style="list-style-type: none"> - with a glass-transition temperature of 210 °C or more, 	Žádost o změnu	Round 2023-07: request for amendment./

			<ul style="list-style-type: none"> - with a weight average molecular weight (Mw) of 35 000 or more but not more than 80 000, - with an inherent viscosity of 0,2 or more but not more than 0,6 dl/gram <p>---</p> <p>Current text: Poly(p-phenylene oxide) in the form of powder</p> <ul style="list-style-type: none"> - with a glasstransitiontemperature of 210 °C, - with a weight average molecular weight (Mw) of 35 000 or more but not more than 80 000, - with an inherent viscosity of 0,2 or more but not more than 0,6 dl/gram 		<p>Round 2022-01- old code 39072020, new code 39072920 (HS 2022). Old code 39072999 -deleted</p> <p>Prolongation Exercise 2020-01-01</p> <p>ROUND 2015-01</p> <p>PPE powder is most commonly mixed in polystyrene, polyamide or other polymer with stabilizing additives flame retardant additives, glass fibres or colour pigment for unique performance characteristics</p>
ex 3919 90 80	51	1702/16/2002 PROLONG 2019	<p>DE(15.09.2022) request for amendment: Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50µm or more but not exceeding 125 µm</p> <p>---</p> <p>Current text: Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 µm or more but not exceeding 90 µm, covered on one side with an adhesive layer and a release sheet</p>	Žádost o změnu	<p>Round 2023-07- request for amendment.//</p> <p>Prolongation Exercise 2019-01-01//</p> <p>HS 2016 3919 90 00--> 3919 90 80//</p> <p>Prolongation Exercise 1/1/2014</p>
ex 7019 61 00 ex 7019 63 00	70 30	1290020/2016 PROLONG 2022	<p>NL(11.10.2022) request for amendment: E-fibre glass fabrics:</p> <ul style="list-style-type: none"> - having a weight of 20 g/m² or more, but not more than 214 g/m², - surface treated with an organosilane coupling agent, - in rolls, - having a humidity content by weight of 0,13 % or less, and - having not more than 3 hollow fibres out of 100 000 fibres, <p>for the exclusive use in the manufacture of prepregs and copper clad laminates</p> <p>---</p> <p>Current text: E-fibre glass fabrics:</p> <ul style="list-style-type: none"> - having a weight of 20 g/m² or more, but not more than 214 g/m², - impregnated with silane, 	Žádost o změnu	<p>Round 2023-07: request for amendment.</p> <p>Round 2022-01 - old codes 70195200 and 70194000, new codes 70196100 and 70196300 (HS 2022).</p> <p>Prolongation Exercise 2022-01-01</p> <p>Round 2020-01 Supplementary unit to be added</p> <p>Round 2019-07 Transferred from quota to suspension. The tariff quota is set to deleted</p> <p>Round 2019-01: Request for prolongation</p> <p>ROUND 2017-07 resubmission</p> <p>ROUND 2017-01</p>

			<ul style="list-style-type: none"> - in rolls, - having a humidity content by weight of 0,13 % or less, and - having not more than 3 hollow fibres out of 100 000 fibres, for the exclusive use in the manufacture of prepregs and copper clad laminates (1)		Glasgewebe in Rollen
ex 8408 90 65 ex 8408 90 67 ex 8408 90 81	20 20 20	5950533/2021	<p>AT(13.09.2022) request for amendment: Compression-ignition internal combustion piston engines:</p> <ul style="list-style-type: none"> - of the inline type, - with a cylinder capacity of 7 000 cm³ or more but not more than 18 100 cm³, - with a power of 205 kW or more but not more than 597 kW, - with an exhaust after-treatment module, - with external width/height/depth dimensions of not more than 1 310/1 300/1 040 mm or 2 005/1 505/1 300 mm or 2 005/1 505/1 800 mm, for use in the manufacture of crushing, screening, separation or compost turning machines --- <p>Current text description: Compression-ignition internal combustion piston engines:</p> <ul style="list-style-type: none"> - of the inline type, - with a cylinder capacity of 7 100 cm³ or more but not more than 18 000 cm³, - with a power of 205 kW or more but not more than 597 kW, - with an exhaust after-treatment module, - with external width/height/depth dimensions of not more than 1 310/1 300/1 040 mm or 2 005/1 505/1 300 mm or 2 005/1 505/1 800 mm, for use in the manufacture of crushing, screening or separation machines (1)	Žádost o změnu	Round 2023-07 - request for amendment./ Round 2022/7 Diesel engine for hydraulic, mechanical or generator drives in machines for the treatment of solid waste, biomass or compost
ex 8501 10 99	75	1093188/2015 PROLONG 2021	<p>HU (14.09.2022) request for amendment: Permanently excited DC motor with</p> <ul style="list-style-type: none"> - a multiple-phase winding, - an external diameter of 24 mm or more but not more than 38 mm, - a rated speed of not more than 12 000 rpm, - a power supply voltage of 8 V or more but not more than 27 V 	Žádost o změnu	Round 2023-07: Request for amendment./ Prolongation Exercise 2021-01-01/ ROUND 01-2016 Motor for actuator

			<p>---</p> <p>Current text: Permanently excited DC motor with</p> <ul style="list-style-type: none"> - a multiple-phase winding, - an external diameter of 28 mm or more but not more than 35 mm, - a rated speed of not more than 12 000 rpm, - a power supply voltage of 8 V or more but not more than 27 V 		
ex 8501 10 99	79	1805/10/2003 PROLONG 2019	<p>HU(14.09.2022): request for amendment: DC motor with brushes and an internal rotor with a three-phase winding, whether or not equipped with a worm or a pinion, of a specified temperature range covering at least - 20°C to + 70°C</p> <p>---</p> <p>Current text: DC motor with brushes and an internal rotor with a three-phase winding, whether or not equipped with a worm, of a specified temperature range covering at least - 20 °C to + 70 °C</p>	Žádost o změnu	<p>Round 2023-07 -Request for amendment./ Round 2020-01 -Request for amendment./</p> <p>Prolongation Exercise 2019-01-01 Prolongation Exercise 1/1/2014</p>
ex 8505 19 10	20	2200205/2019	<p>SL (12.09.2022) request for removal of the end-use requirement: Arc segments of permanent magnets of agglomerated ferrite, with:</p> <ul style="list-style-type: none"> - a length of 16,8 mm or more, but not more than 110,2 mm, - a width of 14,8 mm or more, but not more than 75,2 mm, and - a thickness of 4,8 mm or more, but not more than 13,2 mm <p>---</p> <p>Current text: Arc segments of permanent magnets of agglomerated ferrite, with:</p> <ul style="list-style-type: none"> - a length of 16,8 mm or more, but not more than 110,2 mm, - a width of 14,8 mm or more, but not more than 75,2 mm, - a thickness of 4,8 mm or more, but not more than 13,2 mm, <p>for use in the manufacture of electromotor rotors for ventilation and air-conditioning systems (1)</p>	Žádost o změnu	<p>Round 2023-07: request for amendment./ Round 2020-01 meant to be installed on rotor of electromotor that is used in applications in ventilation and air-conditioning systems</p>
ex 8507 60 00	33	1232310/2015	<p>NL(14.09.2022) request for amendment: Lithium-ion accumulator, with:</p>	Žádost o změnu	<p>Round 2023-07:request for amendment.</p>

			<ul style="list-style-type: none"> - a length of 150 mm or more, but not more than 1 310 mm, - a width of 100 mm or more, but not more than 1 000 mm, - a height of 200 mm or more, but not more than 1 500 mm, - a weight of 75 kg or more, but not more than 200 kg, - a nominal capacity not less than 58 Ah and not more than 500 Ah - a nominal output voltage of 230V AC (line to neutral) or a nominal voltage of 50V (± 10 %) <p>----</p> <p>Current text: Lithium-ion accumulator, with:</p> <ul style="list-style-type: none"> - a length of 150 mm or more, but not more than 1,000 mm, - a width of 100 mm or more, but not more than 1,000 mm, - a height of 200 mm or more, but not more than 1,500 mm, - a weight of 75 kg or more, but not more than 200 kg, - a nominal capacity not less than 150Ah and not more than 500 Ah, - a nominal output voltage of 230V AC (Line to neutral) or a nominal voltage of 64V (±10 %) 		<p>Round 2023-01 - review of the suspension</p> <p>Round 2022-01: review of the measure. Round 2021-01: review of the measure. Round 2020-07 - Objection- withdrawn. Round 2020-01- Amendment - duty rate set to 1,3%. ROUND 07/2019: request for amendment</p> <p>ROUND 01-2016 The product is a battery pack for use in a stationary energy storage application.</p>
ex 8536 49 00	50	1940311/2019	<p>TR(14.09.2022) request for amendment: Relay in the shape of a cube with:</p> <ul style="list-style-type: none"> - a coil operating voltage of 12 VDC or more, but not more than 24 VDC, - a contact current carrying capacity of 5A or more, but not more than 15A, - a contact voltage of 80 VAC or more, but not more than 270 VAC - outer dimensions of 19 mm (± 0,4 mm) X 15,2 mm (± 0,4 mm) X 15,5 mm(± 0,4 mm) <p>for use in the production of control board of white goods</p> <p>-----</p> <p>Current text: Relay with:</p> <ul style="list-style-type: none"> - a contact current carrying capacity of 5 A or more but not more than 15 A, - a nominal voltage of 80 V or more but not more than 270 V, and - outer dimensions of 19 mm x 15,2 mm x 15,5 mm, <p>for use in the manufacture of control boards for household appliances</p>	Žádost o změnu	<p>Round 2023-07- requests for amendment. Round 2020-01 for use in the production of control boards of white goods</p>

			(1)		
ex 8537 10 98	50	3033461/2014 PROLONG 2020	<p>SK(12.09.2023) request for amendment: Electronic control unit (BCM (Body Control Module, IBU (Integrated Body Control Module), or similar):</p> <ul style="list-style-type: none"> - comprising at least: plastic box with printed circuit board - whether or not with metal holder, with voltage of 9 VDC or more, but not more than 16 VDC (direct current voltage), - able to control, evaluate and manage functions of assisting services in an automobile, at least wiper timing, window heating, interior lighting, seat belt reminder, <p>of a kind used in the manufacture of goods of Chapter 87</p> <p>---</p> <p>Current text: Electronic control unit BCM (Body Control Module) comprising</p> <ul style="list-style-type: none"> - plastic box with printed circuit board and metal holder, - with voltage of 9V or more, but not more than 16V, - able to control, evaluate and manage functions of assisting services in an automobile, at least wiper timing, window heating, interior lighting, seat belt reminder <p>of a kind used in the manufacture of goods of Chapter 87</p>	Žádost o změnu	Round 2023-07- Request for amendment./ Prolongation Exercise 2020-01-01/ Round 2017-01 :CN change 8537 10 99 50 -> 8537 10 98 50 ROUND 2015-07 Electronic control unit will be placed in the dashboard of a car.
ex 8540 91 00	20	4610399/2017 PROLONG 2023	<p>AT(13.09.2022) request for amendment: Thermionic electron source (emitter point) of lanthanum hexaboride (CAS RN 12008-21-8) or cerium hexaboride (CAS RN 12008-02-5), with or without a metal housing with electric connectors having</p> <ul style="list-style-type: none"> - a graphite carbon shield mounted in a mini-Vogel type system, - separate pyrolytic carbon blocks used as heating elements, and - a cathode temperature of less than 1 800 K at a filament current of 1,26 A <p>----</p> <p>Current text: Thermionic electron source (emitter point) of lanthanum hexaboride (CAS RN 12008-21-8) or cerium hexaboride (CAS RN 12008-02-5), in a metal housing with electric connectors having</p> <ul style="list-style-type: none"> - a graphite carbon shield mounted in a mini-Vogel type system 	Žádost o změnu	Round 2023-07; request for amendment./ Prolongation Exercise 2023-01-01 ROUND 2018-07 for incorporation into a cathode ray tube for raster electron microscopes, semiconductor inspection systems or electron beam lithography devices.

			<ul style="list-style-type: none"> - separate pyrolytic carbon blocks used as heating elements and - a cathode temperature of less than 1800 K at a filament current of 1,26 A 		
ex 8708 40 20	80	5701899/2021	<p>SK(12.09.2022) request for amendment: Transmission gearbox without torque converter, with:</p> <ul style="list-style-type: none"> - dual clutch, - 7 or more forward gears, - 1 reverse gear, - a maximum torque of 390 Nm, - whether or not with electric motor integrated, - a height of 400 mm or more but not more than 600 mm, - a width 350 mm or more but not more than 600 mm, and - a weight of 70 kg or more but not more than 110 kg, <p>for use in the manufacture of motor vehicles of Heading 8703</p> <p>---</p> <p>Current text: Transmission gearbox without torque converter, with:</p> <ul style="list-style-type: none"> - dual clutch, - 7 or more forward gears, - 1 reverse gear, - a maximum torque of 390 Nm, - whether or not with electric motor integrated, - a height of 480 mm or more but not more than 600 mm, - a width of 350 mm or more but not more than 450 mm, and - a weight of 80kg or more but not more than 110 kg, <p>for use in the manufacture of motor vehicles of Heading 8703 (1)</p>	Žádost o změnu	<p>Round 2023-07: request for amendment.// Round 2023-01 adding supplementary unit - p/st./ Round 2022/7</p> <ul style="list-style-type: none"> • The component is to be used as an Automotive Transmission part, specifically as a Gearbox for Petrol and Hybrid Cars of 8703.
ex 8714 99 50 ex 8714 99 50	11 91	1550343/2019	<p>Derailleur gears, consisting of:</p> <ul style="list-style-type: none"> - rear derailleur and mounting articles, - with or without front derailleur, <p>for use in the manufacture of bicycles (including electric bicycles) (1)</p>	Žádost o změnu	<p>Round 2023-07: adding supplementary unit pieces. Round 2020-01 The derailleur is a change-over-gear shifter used in the bicycles; Used in the manufacture of bicycles</p>

ex 8714 99 90	40	1550250/2019	Stem for bicycle handlebars, for use in the manufacture of bicycles (including electric bicycles) (1)	Žádost o změnu	Round 2023-07: Adding supplementary unit p/st.// Round 2020-01 used in the manufacture of bicycles
ex 9002 11 00	23	1794993/2020	DE(15.09.2023): Lens with: <ul style="list-style-type: none"> - motorized focus, zoom, aperture, - electronically switchable infrared cut filter, - an adjustable focal length not less than 2,7 mm and not more than 55mm, - a weight of not more than 120 g, - a length of less than 70 mm, - a diameter of not more than 70 mm <p>---</p> Current text <p>Lenses with:</p> <ul style="list-style-type: none"> - motorized focus, zoom, aperture, - electronically switchable infrared cut filter, - an adjustable focal length not less than 2,7 mm and not more than 55 mm, - a weight of not more than 100 g, - a length of less than 70 mm, - a diameter of not more than 60 mm 	Žádost o změnu	Round 2023-07 - request for amendment./ Round 2021-01 Intended use: assembly in cctv cameras.

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1)